

SC190 to SC925

Miniature Shock Absorbers

Long stroke and soft contact

Self-compensating, soft contact

Energy capacity 25 Nm/cycle to 110 Nm/cycle

Stroke 16 mm to 40 mm

SC190EUM (0 to 4)

SC300EUM (0 to 4)

SC650EUM (0 to 4)

SC925EUM (0 to 4)

The identification numbers listed are the respective standard units of the corresponding shock absorber series. Special types can have deviating identification numbers.




Table of contents	Page
General instructions.....	2
Safety information	2
Intended use.....	2
Description and function.....	2
Calculation and design	2
Delivery and storage	2
Maintenance and care.....	2
Disassembly and disposal.....	2
Mounting instructions.....	3 - 6
Warranty	7
Expected service life.....	7
Technical data.....	7

Manual

General instructions

This manual is for the disruption-free use of the product types listed on page 1; its compliance is a prerequisite for the fulfilment of any warranty claims.


Therefore, make sure to read this manual before use.

Please always maintain the specified limits from the performance table (technical data). Take into account the predominant environmental conditions and restrictions.

Note the regulations of the trade association, TÜV or corresponding national, international and European regulations. Installation and commissioning only according to mounting instructions.

constant over the entire stroke. A requirement for a constant rate of deceleration is the correct calculation of the industrial shock absorber and therefore the correct selection of the right metering orifice pattern or the right hardness level of the shock absorber. The hardresses are graded from zero (soft) to four (hard).

General Function




F = Force (N) p = Internal pressure (bar) s = Stroke (m)
t = Deceleration time (s) v = Velocity (m/s)

Safety information

WARNING

If ACE miniature shock absorbers are used where a failure of the product could lead to personal injuries and/or material damage, additional safety elements must be implemented.

Free-moving masses can lead to injuries by crushing during installation of the shock absorber. Secure moving masses against inadvertent starting with suitable safety precautions before installing the shock absorbers.



* The load velocity reduces continuously as you travel through the stroke due to the reduction in the number of metering orifices (*) in action. The internal pressure remains essentially constant and thus the Force vs. stroke curve remains linear.

Intended use

ACE miniature shock absorbers are used wherever moving masses are to be slowed down in a defined end position. The industrial shock absorbers are designed for force capacity in an axial direction. Within the permissible load limits the industrial shock absorber also acts as a stop.

Description and function

The ACE miniature shock absorbers SC190 to SC925 are maintenance-free, ready-to-install hydraulic components with numerous metering openings.

During the slowing down process the moving mass moves with kinetic energy and, if necessary, an additional drive energy in the axial direction of the piston rod with a defined impact velocity against the rod end button of the shock absorber. Alternatively, numerous shock absorbers can also be used in parallel. During the initiated slowing down process the piston rod is pushed into the shock absorber. The hydraulic oil located before the piston is displaced through all metering orifices at the same time. The number of effective metering openings reduces in proportion to the driven stroke. The retraction speed reduces. The dynamic pressure applied in front of the piston corresponds to the counter-force applied by the shock absorber and remains approximately

Calculation and design

In order to ensure an optimum, fault-free and durable function of the industrial shock absorbers they must be correctly dimensioned and designed. The following parameters must be known and used in the calculation:

- Moving mass [kg]
- Impact velocity of the mass into the shock absorber(s) [m/s]
- Additionally acting propelling force, propelling power or propelling torque [N, kW, Nm]
- Number of shock absorbers acting in parallel [n]
- Number of strokes or cycles per hour [1/h]

The correct size of the shock absorbers can be determined with the ACE online calculation programme at www.ace-ace.de. You can also send us the completed online form via e-mail for checking.

Or make use of our free calculation service by phoning: +49 (0)2173 - 9226-20.

WARNING

The dampers must be dimensioned in such a way that the calculated values do not exceed the maximum values of the respective performance table (technical data):

W₃ [Nm/cycle]

W₄ [Nm/h]

Effective weight me

Max. side load angle [°]

For a correct damping design the shock absorber must represent the only braking system. Additional braking systems, such as a pneumatic end position damping length, must not overlap with the end position damping length by the shock absorber and must be disabled.

Delivery and storage

- After delivery please check the shock absorber for any damage.
- The shock absorber can become damaged if it falls. Carefully remove shock absorber from the packaging.
- Shock absorbers can generally be stored in any position.
- Storage in the original packaging is preferred.
- Always store shock absorbers in a dry place in order to avoid oxidation.
- The recommended maximum storage time is three years.

Maintenance and care

Regularly check the shock absorbers for oil loss, return of the piston rod and external damage.

Shock absorbers are machine elements that are subject to continuous wear. Increased service life results in reduced damping effect. If this is no longer sufficient, the shock absorbers must be replaced or exchanged as appropriate.

Disassembly and disposal

Take account of environmental protection (recovery of problematic substances) during disposal of the shock absorber.

The SC miniature shock absorbers are filled with temperature stable oil. The corresponding data sheet is available on request. Faulty dampers can be sent to our service department for determination of the cause of failure.

Mounting instructions and mounting accessories

Installation instructions

Before installation and use check whether the identification number on the damper or on the packaging matches the respective designation on the delivery note. Industrial shock absorbers are maintenance-free and ready to install.

Operating temperature range: 0 °C to 66 °C

Mounting: As required but always in such a way that the entire damper stroke is used. The dampers must always be mounted in such a way that the forces are introduced centrally over the piston rod. The maximum permissible side load angle of 5° must not be exceeded. If there is a side load angle, it generally leads to a reduction in service life. In the case of maximum permissible values being exceeded a side load adapter must be used.

WARNING	
	Temperature effect: The W_4 and m_e values given in the performance table (see manual or catalogue) are valid for room temperature. Deviating values apply to higher temperatures.
	During installation of the dampers moving masses can lead to injuries due to inadvertent starting. Secure moving masses against inadvertent moving.
	The dampers may be unsuitable for use and have an insufficient damping effect. Check the specific suitability of the dampers before installation.
	If operated outside of the operating temperature range, the damper can lose its function. Operating temperature range must be maintained. Do not paint dampers due to heat emission.
	Fluids, gases and dirt particles in the surrounding area can attack or destroy the seal system of the damper and cause it to fail. Protect or encapsulate piston rod and seal system from external materials in the surrounding area.
	Damage to the piston rod surface can destroy the seal system. Do not grease, oil piston rod etc. and protect against dirt particles.
	The piston rod can be torn from the damper. Do not load the piston rod with tensile stress.
	Damper can tear off upon impact. Always lay out the connection structure in such a way that the maximum occurring forces can be absorbed with sufficient safety. The maximum reacting forces listed in the calculation range may deviate from the actually occurring reacting forces, as these are based on theoretical values.

Commissioning

- After installation, start a test run of the moving mass at reduced operating speed to begin with.

During the test run

- Gradually accelerate the load capacity up to the subsequent operating speed. You can find this in the calculation for your application. In the correct final setting, the piston rod of the shock absorber reaches the end position (positive stop) without a hard stop.

M14x1.5 mounting accessories

SC190; 0 to 4

Before installation check whether the identification number on the packaging matches the respective designation on the delivery note.


Note the dimensioning for mounting when using accessory parts. Bolts for fitting of accessories are not included.

If you have any questions, please phone +49 (0)2173 - 9226-20 for free advice.

When using accessory parts and mounting elements also note the mounting instructions for accessories delivered separately.


MB14

Clamp mount





RF14

Rectangular flange




UM14

Universal mount




Mounting types


Use of clamp mount MB



Use of rectangular flange RF




Screwing the damper into a threaded hole with additional locknut




With screw-in lengths
> 19 mm, the thread-
hole should be made
according to the
ISO3 6G.

Mounting of damper in borehole with two locknuts



Torque:
KM14 = 12.9-14.1 Nm

Use of universal mount UM



Torque:
KM14 = 12.9-14.1 Nm

Packaging disposal

Please dispose of the transportation packaging in an environmentally-friendly manner. Recycling packaging materials saves raw materials and reduces waste. The packaging materials do not contain any prohibited materials.

Mounting instructions and mounting accessories

Installation instructions

Before installation and use check whether the identification number on the damper or on the packaging matches the respective designation on the delivery note. Industrial shock absorbers are maintenance-free and ready to install.

Operating temperature range: 0 °C to 66 °C

Mounting: As required but always in such a way that the entire damper stroke is used. The dampers must always be mounted in such a way that the forces are introduced centrally over the piston rod. The maximum permissible side load angle of 5° must not be exceeded. If there is a side load angle, it generally leads to a reduction in service life. In the case of maximum permissible values being exceeded a side load adapter must be used.

M20x1.5 mounting accessories


SC300; 0 to 4

Before installation check whether the identification number on the packaging matches the respective designation on the delivery note.

Note the dimensioning for mounting when using accessory parts. Bolts for fitting of accessories are not included.

If you have any questions, please phone +49 (0)2173 - 9226-20 for free advice.

When using accessory parts and mounting elements also note the mounting instructions for accessories delivered separately.




WARNING

- Temperature effect:** The W_4 and m_e values given in the performance table (see manual or catalogue) are valid for room temperature. Deviating values apply to higher temperatures.
- During installation of the dampers moving masses can lead to injuries due to inadvertent starting. Secure moving masses against inadvertent moving.**
- The dampers may be unsuitable for use and have an insufficient damping effect. Check the specific suitability of the dampers before installation.**
- If operated outside of the operating temperature range, the damper can lose its function. Operating temperature range must be maintained. Do not paint dampers due to heat emission.**
- Fluids, gases and dirt particles in the surrounding area can attack or destroy the seal system of the damper and cause it to fail. Protect or encapsulate piston rod and seal system from external materials in the surrounding area.**
- Damage to the piston rod surface can destroy the seal system. Do not grease, oil piston rod etc. and protect against dirt particles.**
- The piston rod can be torn from the damper. Do not load the piston rod with tensile stress.**
- Damper can tear off upon impact. Always lay out the connection structure in such a way that the maximum occurring forces can be absorbed with sufficient safety. The maximum reacting forces listed in the calculation range may deviate from the actually occurring reacting forces, as these are based on theoretical values.**


MB20

Clamp mount




RF20

Rectangular flange




UM20

Universal mount




Mounting types


Use of clamp mount MB




Use of rectangular flange RF




Screwing the damper into a threaded hole with additional locknut



Mounting of damper in borehole with two locknuts



Use of universal mount UM



Commissioning

- After installation, start a test run of the moving mass at reduced operating speed to begin with.

During the test run

- Gradually accelerate the load capacity up to the subsequent operating speed. You can find this in the calculation for your application. In the correct final setting, the piston rod of the shock absorber reaches the end position (positive stop) without a hard stop.

Packaging disposal

Please dispose of the transportation packaging in an environmentally-friendly manner. Recycling packaging materials saves raw materials and reduces waste. The packaging materials do not contain any prohibited materials.

Mounting instructions and mounting accessories

Installation instructions

Before installation and use check whether the identification number on the damper or on the packaging matches the respective designation on the delivery note. Industrial shock absorbers are maintenance-free and ready to install.

Operating temperature range: 0 °C to 66 °C

Mounting: As required but always in such a way that the entire damper stroke is used. The dampers must always be mounted in such a way that the forces are introduced centrally over the piston rod. The maximum permissible side load angle of 5° must not be exceeded. If there is a side load angle, it generally leads to a reduction in service life. In the case of maximum permissible values being exceeded a side load adapter must be used.

M25x1.5 mounting accessories


SC650; 0 to 4

Before installation check whether the identification number on the packaging matches the respective designation on the delivery note.

Note the dimensioning for mounting when using accessory parts. Bolts for fitting of accessories are not included.

If you have any questions, please phone +49 (0)2173 - 9226-20 for free advice.

When using accessory parts and mounting elements also note the mounting instructions for accessories delivered separately.




WARNING

- Temperature effect:** The W_4 and m_e values given in the performance table (see manual or catalogue) are valid for room temperature. Deviating values apply to higher temperatures.
- During installation of the dampers moving masses can lead to injuries due to inadvertent starting. Secure moving masses against inadvertent moving.**
- The dampers may be unsuitable for use and have an insufficient damping effect. Check the specific suitability of the dampers before installation.**
- If operated outside of the operating temperature range, the damper can lose its function. Operating temperature range must be maintained. Do not paint dampers due to heat emission.**
- Fluids, gases and dirt particles in the surrounding area can attack or destroy the seal system of the damper and cause it to fail. Protect or encapsulate piston rod and seal system from external materials in the surrounding area.**
- Damage to the piston rod surface can destroy the seal system. Do not grease, oil piston rod etc. and protect against dirt particles.**
- The piston rod can be torn from the damper. Do not load the piston rod with tensile stress.**
- Damper can tear off upon impact. Always lay out the connection structure in such a way that the maximum occurring forces can be absorbed with sufficient safety. The maximum reacting forces listed in the calculation range may deviate from the actually occurring reacting forces, as these are based on theoretical values.**


MB25

Clamp mount




RF25

Rectangular flange




UM25

Universal mount




Mounting types


Use of clamp mount MB



Use of rectangular flange RF




Screwing the damper into a threaded hole with additional locknut




Torque:
KM25 = 60-66 Nm
Minimum screw-in depth:
1.5 x bolt diameter

Mounting of damper in borehole with two locknuts



Torque:
KM25 = 60-66 Nm

Use of universal mount UM



Torque:
KM25 = 60-66 Nm

Commissioning

- After installation, start a test run of the moving mass at reduced operating speed to begin with.

During the test run

- Gradually accelerate the load capacity up to the subsequent operating speed. You can find this in the calculation for your application. In the correct final setting, the piston rod of the shock absorber reaches the end position (positive stop) without a hard stop.

Packaging disposal

Please dispose of the transportation packaging in an environmentally-friendly manner. Recycling packaging materials saves raw materials and reduces waste. The packaging materials do not contain any prohibited materials.

Mounting instructions and mounting accessories

Installation instructions

Before installation and use check whether the identification number on the damper or on the packaging matches the respective designation on the delivery note. Industrial shock absorbers are maintenance-free and ready to install.

Operating temperature range: 0 °C to 66 °C

Mounting: As required but always in such a way that the entire damper stroke is used. The dampers must always be mounted in such a way that the forces are introduced centrally over the piston rod. The maximum permissible side load angle of 5° must not be exceeded. If there is a side load angle, it generally leads to a reduction in service life. In the case of maximum permissible values being exceeded a side load adapter must be used.

M25x1.5 mounting accessories


SC925; 0 to 4

Before installation check whether the identification number on the packaging matches the respective designation on the delivery note.

Note the dimensioning for mounting when using accessory parts. Bolts for fitting of accessories are not included.

If you have any questions, please phone +49 (0)2173 - 9226-20 for free advice.

When using accessory parts and mounting elements also note the mounting instructions for accessories delivered separately.




WARNING

- Temperature effect:** The W_4 and m_e values given in the performance table (see manual or catalogue) are valid for room temperature. Deviating values apply to higher temperatures.
- During installation of the dampers moving masses can lead to injuries due to inadvertent starting. Secure moving masses against inadvertent moving.**
- The dampers may be unsuitable for use and have an insufficient damping effect. Check the specific suitability of the dampers before installation.**
- If operated outside of the operating temperature range, the damper can lose its function. Operating temperature range must be maintained. Do not paint dampers due to heat emission.**
- Fluids, gases and dirt particles in the surrounding area can attack or destroy the seal system of the damper and cause it to fail. Protect or encapsulate piston rod and seal system from external materials in the surrounding area.**
- Damage to the piston rod surface can destroy the seal system. Do not grease, oil piston rod etc. and protect against dirt particles.**
- The piston rod can be torn from the damper. Do not load the piston rod with tensile stress.**
- Damper can tear off upon impact. Always lay out the connection structure in such a way that the maximum occurring forces can be absorbed with sufficient safety. The maximum reacting forces listed in the calculation range may deviate from the actually occurring reacting forces, as these are based on theoretical values.**


MB25

Clamp mount




RF25

Rectangular flange




UM25

Universal mount




Mounting types


Use of clamp mount MB




Use of rectangular flange RF




Screwing the damper into a threaded hole with additional locknut



Mounting of damper in borehole with two locknuts



Use of universal mount UM



Commissioning

- After installation, start a test run of the moving mass at reduced operating speed to begin with.

During the test run

- Gradually accelerate the load capacity up to the subsequent operating speed. You can find this in the calculation for your application. In the correct final setting, the piston rod of the shock absorber reaches the end position (positive stop) without a hard stop.

Packaging disposal

Please dispose of the transportation packaging in an environmentally-friendly manner. Recycling packaging materials saves raw materials and reduces waste. The packaging materials do not contain any prohibited materials.

Manual

Warranty

Fundamentally, all modifications to the product by third parties lead to exclusion from the warranty.

Obvious defects must be reported to the vendor in writing immediately after delivery, no later than one week, but in any case before processing or installation, otherwise the assertion of a warranty claim is excluded. A timely dispatch is sufficient to keep the term.

The vendor is to be given an opportunity to check on site. If the complaint is justified the vendor offers warranty by repair or replacement at its own discretion. If the rectification fails, the buyer may choose to demand reduction of payment or cancellation of the contract. If there is only a minor lack of conformity, particularly with only minor defects, the buyer nevertheless has a right of withdrawal.

If, after failed rectification, the buyer chooses to cancel the contract due to a defect of title or material defect, they are not entitled to additionally claim for damages.

If, after failed fulfilment, the buyer chooses compensation, the goods remain with the buyer, if this is reasonable. The compensation is limited to the difference between the purchase price and the value of the defective item. This does not apply if the vendor maliciously causes the breach of contract.

The quality of the goods is only considered as agreed upon with the product description of the vendor. Public statements, claims or advertising of the manufacturer do not represent an additional contractual specification of quality of the goods.

If the buyer receives defective mounting instructions, the buyer is only obligated to deliver defect-free mounting instructions and only if the defect to the mounting instructions prevents proper mounting.

The warranty period is two years and begins upon completion. Exchange and return of custom products are fundamentally excluded. The factory conditions of the manufacturing factory apply to parts not manufactured and processed by the vendor, which can be viewed by the orderer at the vendor at any time. Construction and installation parts are delivered according to the present standard of engineering.

Service life

In general industrial shock absorbers are machine elements that are subject to wear. Wear parts such as seals, pressure chambers and pistons are excluded from the general warranty. The wear of seals is largely dependent upon the operating conditions and the respective application and its operating parameters.

In general with this model of industrial shock absorber with grooved ring wiper seal system an average service life of three to five million load changes can be expected. Adverse environmental and operating conditions can significantly reduce the expected service life.

Performance data

TYPES	Max. energy capacity		Effective Weight				Hardness	Return Force min.	Return Force max.	Return time s	1 Side Load Angle max. °	Weight kg						
	W ₃ Nm/cycle	W ₄ Nm/h	Soft contact		Self-compensating													
			me min. kg	me max. kg	me min. kg	me max. kg												
SC190EUM-0	25	34,000	-	-	0.7	4	-0	4	9	0.25	5	0.08						
SC190EUM-1	25	34,000	2.3	6	1.4	7	-1	4	9	0.25	5	0.08						
SC190EUM-2	25	34,000	5.5	16	3.6	18	-2	4	9	0.25	5	0.08						
SC190EUM-3	25	34,000	14	41	9.0	45	-3	4	9	0.25	5	0.08						
SC190EUM-4	25	34,000	34	91	23.0	102	-4	4	9	0.25	5	0.08						
SC300EUM-0	33	45,000	-	-	0.7	4	-0	5	10	0.10	5	0.18						
SC300EUM-1	33	45,000	2.3	7	1.4	8	-1	5	10	0.10	5	0.18						
SC300EUM-2	33	45,000	7	23	4.5	27	-2	5	10	0.10	5	0.18						
SC300EUM-3	33	45,000	23	68	14.0	82	-3	5	10	0.10	5	0.18						
SC300EUM-4	33	45,000	68	181	32.0	204	-4	5	10	0.10	5	0.18						
SC650EUM-0	73	68,000	-	-	2.3	14	-0	11	32	0.20	5	0.34						
SC650EUM-1	73	68,000	11	36	8.0	45	-1	11	32	0.20	5	0.34						
SC650EUM-2	73	68,000	34	113	23.0	136	-2	11	32	0.20	5	0.34						
SC650EUM-3	73	68,000	109	363	68.0	408	-3	11	32	0.20	5	0.34						
SC650EUM-4	73	68,000	363	1,089	204.0	1,180	-4	11	32	0.20	5	0.34						
SC925EUM-0	110	90,000	8	25	4.5	29	-0	11	32	0.40	5	0.42						
SC925EUM-1	110	90,000	22	72	14.0	90	-1	11	32	0.40	5	0.42						
SC925EUM-2	110	90,000	59	208	40.0	227	-2	11	32	0.40	5	0.42						
SC925EUM-3	110	90,000	181	612	113.0	726	-3	11	32	0.40	5	0.42						
SC925EUM-4	110	90,000	544	1,952	340.0	2,088	-4	11	32	0.40	5	0.42						

¹ If side load angle is higher contact ACE.

Technical data

Energy capacity: 25 Nm/cycle to 110 Nm/cycle

Impact velocity range: 0.15 m/s to 3.66 m/s. Other speeds on request.

Operating temperature range: 0 °C to 66 °C

Mounting: in any position

Positive stop: integrated

Material: Outer body, Accessories: Steel corrosion-resistant coating

Piston rod: Stainless steel, hardened

Rod end button: Hardened steel

Damping medium: Oil, temperature stable

Permissible torque of locknut:

SC190EUM-0 to SC190EUM-4: 12.9 Nm to 14.1 Nm

SC300EUM-0 to SC300EUM-4: 27 Nm to 29.8 Nm

SC650EUM-0 to SC650EUM-4: 60 Nm to 66 Nm

SC925EUM-0 to SC925EUM-4: 60 Nm to 66 Nm

Application field: Linear slides, Pneumatic cylinders, Handling modules, Machines and plant, Finishing and processing centres, Measuring tables, Tool machines

Note: If precise end position datum is required consider use of the stop collar type AH.

Safety instructions: External materials in the surrounding area can attack the sealing components and lead to a shorter service life. Please contact ACE for appropriate solution suggestions. Do not paint the shock absorbers due to heat emission.

On request: Nickel-plated or weartec finish (seawater resistant) or other special options available. Models without rod end button.